

# SAKO SPECIFICATION SAKO

## SAKO 85 SYNTHETIC STAINLESS



SAKO 85 SYNTHETIC STAINLESS has a series of actions which are designated: Short actions Short (S) and Short Magnum (SM), Medium action (M) and Long action (L). All metal parts are made of stainless steel or are specially coated to ensure excellent wear and corrosion resistance in different weather conditions.

The ACTIONS continue to offer traditional SAKO features such as: action sizes matched to cartridges; mechanical ejection and integral tapered scope mount rail. Additionally there is a controlled feed on all models to ensure reliable cartridge feed to the chamber on all situations (Pat. pend.).

The MAGAZINE is detachable and it can also be loaded through the ejection port. Magazine release is prevented against accidental release (Pat.pend.).

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs). All models are available with a single-set trigger as option.

The SAFETY features a mechanism that allows loading and unloading of the rifle with safety engaged.

In two steps injection molded black STOCK has black softer grip areas in the pistol grip and fore-end sides and bottoms. Black outer surfaces are Soft Touch handled.

SAKO 85 SYNTHETIC STAINLESS is available without open sights. Integral rails for the scope mounts are on the top of the receiver.

The totally free-floating BARREL is cold hammer-forged of stainless steel. S and M models available also with short barrel with thread (calibers 338 Federal, 8x57IS, 9.3x62 and 9.3x66 M15x1, other calibers M14x1) at the muzzle for muzzle brake or suppressor assembling.

### TECHNICAL DATA

Action	caliber	rate of twist	Overall length
<b>S</b>	22-250 Rem	14"	S 1075 mm (42 5/16")
	243 Win	10"	S MT 1015 mm (40")
	260 Rem	8"	SM 1125 mm (44 5/16")
	7mm-08 Rem	9.5"	M 1085 mm (42 3/4")
	308 Win	11"	M MT 1025 mm (40 3/8")
	338 Federal	10"	L 1145 mm (45 1/16")
<b>SM</b>	270 Win Short Mag	10"	<b>Barrel length</b>
	300 Win Short Mag	11"	S / M 570 mm (22 7/16")
			S / M MT 510 mm (20")
<b>M</b>	25-06 Rem	10"	SM / L 620 mm (24 3/8")
	6.5x55 SE	8"	<b>Weight</b>
	270 Win	10"	S 2.9 kg (6 3/8 lbs)
	30-06 Sprg	11"	S MT 2.8 kg (6 3/16 lbs)
	8x57IS	9.5"	SM / M 3.0 kg (6 5/8 lbs)
<b>L</b>	9.3x62	14"	M MT 2.9 kg (6 3/8 lbs)
	9.3x66 Sako	14"	L 3.2 kg (7 lbs)
	7mm Rem Mag	9.5"	<b>Length of pull</b>
	300 Win Mag	11"	S / SM / M / L 355 mm (14")
	338 Win Mag	10"	<b>Cartridge capacity</b>
	375 H&H Mag	12"	S / M 6 rounds (1 in chamber, 5 in magazine)
			SM / L 5 rounds (1 in chamber, 4 in magazine)