

SAKO QUAD VARMINT



SAKO QUAD VARMINT rimfire rifle based on P04R action. The gun can be easily converted by customer to calibers 22 LR, 17 Mach 2, 22 WMR or 17 HMR by changing only the barrel and the magazine, if necessary (Pat. pend.). Barrel changing tool included with each rifle.

ACTION

The action is a bolt action design with two locking lugs, bolt lift angle 50°, bolt throw 40 mm (1.60 in) and firing pin travel 5 mm (0.20 in). Ejection is carried out with special spring.

MAGAZINE is 5-round clip magazine for calibers 22 LR and 17 Mach 2 or calibers 22 WMR and 17 HMR. On the bottoms of the magazines are color codes to indicate the applicable calibers. 10-round clip magazine (9-round for cal. 22 WMR and 17 HMR) is also available.

TRIGGER is the same single-stage trigger as on other Sako-rifles. Adjustable from 1 to 2 kg (2 - 4 lbs). Also available with single set trigger mechanism as option.

Sliding safety catch, located rear from the bolt handle, locks the trigger and the bolt.

STOCK

The walnut stock with wide fore-end is oilfinished. Straight stock features ambidextrous palm swell and recoil pad system where length of the pull can be legthened by spacers.

BARRELS

The heavy, free-floating barrels are cold hammer-forced. Barrels are provided with color code rings that indicate caliber of the barrel. Barrels available also with thread 1/2"-20 UNF at the muzzle for silencer mounting.

SIGHTS

SAKO QUAD VARMINT is delivered without open sights. 11mm integral dovetail on the receiver for scope mounting.

Sako Quad scope by Burris with four color coded adjustment rings for respective calibers available as accessory.

Rifle with case for barrels and accessories available as QUAD COMBO.

TECHNICAL DATA

Caliber	rate of twist	Weight	
22 LR	16.5"	Quad	3.5 kg (7 3/4 lbs)
22 WMRF	16"	Overall length	
17 HMR	9"	Quad	1025 mm (40 3/8")
17 Mach 2	9"	Barrel length	
		Quad	560 mm (22")
		Length of pull	
		Quad	345 mm (13 1/2")