

SAKO SPECIFICATION SAKO

SAKO 75 HUNTER STAINLESS



SAKO 75 HUNTER STAINLESS has a series of actions which are designated: Short action I, Medium action III, Long actions IV and V (Magnum). All metal parts are made of stainless steel or are specially coated to ensure excellent wear and corrosion resistance in different weather conditions.

The ACTIONS continue to offer traditional SAKO features such as: action sizes matched to cartridges; mechanical ejection; integral tapered scope mount rail and one-piece forged bolt.

Long and medium bolts are optionally available provided with KEY CONCEPT locking system to prevent illicit use.

The MAGAZINE is detachable and it can also be loaded through the ejection port.

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs). All models are available with a single-set trigger as option.

The SAFETY features a mechanism that allows loading and unloading of the rifle with safety engaged.

The walnut STOCK is oilfinished as standard. Mattelacquered stocks are also available.

Sako 75 Hunter Stainless is supplied WITHOUT OPEN SIGHTS. Integral rails for the scope mounts are on the top of the receiver.

The totally free-floating, stainless steel BARREL is cold-hammerforged.

TECHNICAL DATA

Action	caliber	rate of twist	Overall length
I	222 Rem	14"	I 1060 mm (41 3/4")
	223 Rem	8"	III 1090 mm (42 7/8")
III	22-250 Rem	14"	IV 1110 mm (43 3/4")
	243 Win	10"	V 1160 mm (45 5/8")
	308 Win	11"	Barrel length
IV	25-06 Rem	10"	I 560 mm (22")
	6.5x55 SE	8"	III 570 mm (22 7/16")
	270 Win	10"	IV 580 mm (22 7/8")
	30-06 Sprg	11"	V 620 mm (24 3/8")
	9.3x62	14"	Weight
V	7mm Rem Mag	9.5"	I 2.8 kg (6 3/16 lbs)
	300 Win Mag	11"	III 3.2 kg (7 lbs)
	338 Win Mag	10"	IV 3.5 kg (7 3/4 lbs)
	375 H&H Mag	12"	V 3.8 kg (8 3/8 lbs)
			Cartridge capacity
			I 7 rounds (1 in chamber, 6 in magazine)
			III / IV 6 rounds (1 in chamber, 5 in magazine)
			V 5 rounds (1 in chamber, 4 in magazine)

sako SPECIFICATION sako

SAKO 75 HUNTER STAINLESS



SAKO 75 HUNTER STAINLESS has a series of actions which are designated: Short action I, Medium action III, Long actions IV and V (Magnum). All metal parts are made of stainless steel or are specially coated to ensure excellent wear and corrosion resistance in different weather conditions.

The ACTIONS continue to offer traditional SAKO features such as: action sizes matched to cartridges; mechanical ejection; integral tapered scope mount rail and one-piece forged bolt.

Long and medium bolts are optionally available provided with KEY CONCEPT locking system to prevent illicit use.

The MAGAZINE is detachable and it can also be loaded through the ejection port.

The single-stage TRIGGER pull is adjustable from 1 kg to 2 kg (2 to 4 lbs).

The SAFETY features a mechanism that allows loading and unloading of the rifle with safety engaged.

The walnut STOCK is mattelacquered. Oil finish available as special order.

Sako 75 Hunter Stainless is supplied WITHOUT OPEN SIGHTS. Integral rails for the scope mounts are on the top of the receiver. Standard size blued Sako Optilock scope mounts included with the rifle.

The totally free-floating, stainless steel BARREL is cold-hammerforged.

Sling swivels standard.

TECHNICAL DATA

Action	caliber	rate of twist	Overall length
I	222 Rem *	14"	I 1060 mm (41 3/4")
	223 Rem *	8"	III 1090 mm (42 7/8")
III	22-250 Rem *	14"	IV 1110 mm (43 3/4")
	243 Win *	10"	V 1160 mm (45 5/8")
	7mm-08 Rem *	9.5"	Barrel length
IV	308 Win *	11"	I 560 mm (22")
	25-06 Rem *	10"	III 570 mm (22 7/16")
	6.5x55 SE *	8"	IV 580 mm (22 7/8")
	270 Win	10"	V 620 mm (24 3/8")
	30-06 Sprg	11"	Weight
V	9.3x62 *	14"	I 2.8 kg (6 3/16 lbs)
	7mm Rem Mag	9.5"	III 3.2 kg (7 lbs)
	300 Win Mag	11"	IV 3.5 kg (7 3/4 lbs)
	338 Win Mag	10"	V 3.8 kg (8 3/8 lbs)
	375 H&H Mag *	12"	Cartridge capacity
	* Special order only		I 7 rounds (1 in chamber, 6 in magazine)
			III / IV 6 rounds (1 in chamber, 5 in magazine)
			V 5 rounds (1 in chamber, 4 in magazine)