



## TECHNICAL SPECIFICATION SAKO QUAD RANGE

WEAPON	SAKO QUAD
MODEL	QUAD RANGE
MANUFACTURER	SAKO Ltd., FINLAND
AVAILABLE ACTION SIZES	Right hand / STD Left Hand / -
OPERATION	Manually operated bolt action
BOLT	2 locking lugs, bolt lift angle 50°, spring ejection
CALIBER / RATE OF TWIST	22 LR / 16.5" 22 WMRF / 16" 17 HMR / 9" 17 Mach 2 / 9"
OVERALL WEIGHT w/o ACCESSORIES	4.0 kg (8.8 lbs)
OVERALL LENGTH	1015 mm (39.9")
BARREL LENGTH	560 mm (22")
LENGTH OF PULL	350mm (13.8")
BARREL	Free floating heavy contour barrel (cold hammer forged)
MAGAZINE	Single row metal magazine
MAGAZINE CAPACITY	10 round magazine (9 round for cal. 17 HMR)
SIGHTS	No open sights
OPTICAL SIGHT ATTACHMENT	Dovetail style rail
METAL PARTS SURFACE FINISHING	Blued metal parts
STOCK	Matte laminate stock
TRIGGER MECHANISM	Single stage trigger adjustable 1 to 2kg (2 to 4 lbs) (Optional set trigger)
SAFETY	Two stage safety
ACCESSORIES	T25 torx key Manual

